



BEARING BOWER CORP.

28,575 mm x 68,262 mm x 22,225 mm NTN 4T-M88040/M88010 tapered roller bearings



Bearing No. 4T-M88040/M88010

4T-M88040/M88010 Bearing 2D drawings and 3D CAD models

Size	28.575x68.262x22.225 mm
Bore Diameter	28,575 mm
Outer Diameter	68,262 mm
Width	22,225 mm
d	28,575 mm
D	68,262 mm
T	22,225 mm
B	22,225 mm
C	17,462 mm
a	19.3 mm
rs min	2.3 mm
r1s min	1.5 mm
e	0.18
Y2	1.1
Y0	0.6
Mass	0.41 kg
Dynamic load, C	57.5 kN
Rating life coefficient, A2	1.4
Static load, C0	73.5 kN
Nlim (oil)	8,100 rpm
Nlim (grease)	6,100 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage	0.43 Hz



BEARING BOWER CORP.

frequency, FTF	
Characteristic rolling element frequency, BSF	6.69 Hz
Characteristic outer ring frequency, BPF0	7.77 Hz
Characteristic inner ring frequency, BRFI	10.23 Hz
ra max	2.3 mm
r1a max	1.5 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.428
Product Group	B04334